

The flexibility of reefer containers over reefer vessels has added to the increased popularity of this product which is available in 40ft high cube SeaFresh marine and 45ft high cube SeaFresh Intermodal containers. Other sizes are available upon request.



- Structure filled using high-tec 'even flow' insulation to ensure no airpockets and full adhesion to eliminate de-lamination
- Anti corrosion materials used throughout to maximise container life
- Stainless steel internal lining
- CFC free 'ozone friendly' refrigerant
- Microprocessor temperature control to hold temperature within very close tolerance
- Microprocessor retains operational history to assist with trouble shooting and cargo monitoring
- Sub floor corrugated pressing to eliminate damage and give maximum floor support

In addition a range of refrigerated machinery is available to suit individual operator's requirements.

Specification	40ft High Cube	45ft High Cube
External Length (mm)	12,192	13,716
Width	2,438	2,556
Height	2,896	2,896
Internal Length	11,584	13,280
Width	2,294	2,435
Height	2,557	2,582
Cubic Capacity (m ³)	67.9	83.5
Euro pallets	22	33
Maximum gross weight (kg)	34,000	34,000
Tare (kg)	4,800	5,990
Payload (kg)	29,200	28,010
Gooseneck tunnel	Fitted	Fitted
Refrigerated machinery	Customer choice	Thermo King Magnum SL

Actual measurements and other specification details may vary from those shown due to Sea Axis's policy of continual product development.

For further information on SeaFresh please contact your nearest office or agent. For full list of contacts visit www.sea-axis.com