

# sea axis

# SeaRack

The SeaAxis 40ft SeaRack gives shippers and manufacturers maximum flexibility for transporting non-standard or awkward shaped freight such as machinery, earth moving equipment, long pipes and lumber.



The end walls fold flush into the deck so that SeaRack can be used either with end walls up as a flatrack, or with end walls down as a platform flat. To comply with requirements for a drivers cab 'headache' board, the option also exists to have one end up and other end down simultaneously.

The SeaRack can be used as a temporary tweendeck for large, indivisible loads, when units are positioned on hatch covers.

- Stanchion pockets fitted for load security
- Fully equipped with lashing points for tie down of cargo
- Fliplocks enable SeaRack to be interlocked with other designs of 40ft flatracks
- Endwall lock down mechanism to prevent unexpected end wall lifting. Easily inspected end wall locking and interlocking mechanism so operator can ensure that all locks are correctly engaged

Specification	40ft
<b>External Dimensions (mm)</b>	
Length	12,192
Width	2,438
Height	2,591
<b>Internal Dimensions (mm)</b>	
Length	12,078
Width	2,364
Side opening length	11,757
Height	1,943
<b>Maximum Gross Weight (kg)</b>	45,000
<b>Tare (kg)</b>	5,300
<b>Payload (kg)</b>	39,700
<b>Interlock into 8ft 6</b>	4
<b>Fork tunnel</b>	Fitted
<b>Gooseneck tunnel</b>	Fitted

Actual measurements and other specification details may vary from those shown due to Sea Axis's policy of continual product development.

For further information on SeaRack please contact your nearest office or agent. For full list of contacts visit [www.sea-axis.com](http://www.sea-axis.com)

specialist marine container leasing